



# Mr. Heater MH40 Radiant Overhead Heater

<b>BTU per Hour</b>	40,000
<b>Heating Area (Sq Ft)</b>	750
<b>Tank Capacity (Min)</b>	40# Propane Cylinder – relevant to LP version only
<b>Run Time (Hrs at Max BTU)</b>	No
<b>Run Time (Hrs at Min BTU)</b>	No
<b>Fuel Consumption/Burn Rate (Gal/Hr)</b>	No
<b>Electricity Required</b>	No
<b>Maximum Elevation (Ft)</b>	No
<b>Weight (Lbs)</b>	28.20
<b>Model</b>	MH40NG or MH40LP
<b>Oversized</b>	No
<b>Length</b>	35.50
<b>Width</b>	12.50
<b>Height</b>	No
<b>Disclaimer</b>	Do not use in sleeping quarters, mobile homes, or recreational vehicles. For elevations above 2,000ft ratings should be reduced at the rate of 4% for each 1,000ft above sea level or as specified by local authority having jurisdiction.
<b>Use</b>	Loading Docks, Warehouses, Factory Production and Assembly Areas, Animal Pens and Stalls, Automotive Repair Shops, Sporting Arenas, Public Entranceways
<b>Safety Tip-Over Switch</b>	No
<b>Thermostat</b>	Yes
<b>Brand</b>	Mr. Heater
<b>Oxygen Depletion Sensor (ODS)</b>	No
<b>Warranty</b>	1 Year Limited
<b>Hose &amp; Regulator Included</b>	No
<b>Fuel Type</b>	Natural Gas
<b>Heat Type</b>	Radiant
<b>High Limit Safety Shut-off (HLS)</b>	No
<b>Ignition</b>	Match Lit
<b>Indoor Safe</b>	Yes