

EFFICIENT RADIANT HEAT

Model #	Description
F170800	HS125LP - Portable Propane Radiant - 125,000 BTU/Hr.
F170850	HS125NG - Portable Natural Gas Radiant - 125,000 BTU/Hr.

- Heats Up to 3,125 Sq. Ft.
- Rugged, Durable Construction
- No Electricity Required
- Welded Frame, Heat Shield, Safety Shut-Off, Regulator
- P.O.L. Connection with 10' Hose Included
- Recommended for Operation On Tanks 100 Lbs. and Larger
- Fully Assembled - Ready to Use
- Includes Handles
- Runs Up to 17 Hrs. On a 100 Lb. Tank
- CSA Certified



SPECIFICATIONS:	HS35LP	HS125LP	HS125NG
Stock Number	F170700	F170800	F170850
Output (BTU/HR)	35,000	125,000	125,000
Heating Area (SQ. FT.)	875	3125	3125
Fuel	Propane	Propane	Natural Gas
Propane Consumption (LBS/HR)	1.6 max	5.8 max	N/A with Natural Gas
Pressure Regulator Settings	22" w.c.	13.5" w.c.	7" w.c.
Flame Safety	Thermocouple Operated Gas Valve	Thermocouple Operated Gas Valve	Thermocouple Operated Gas Valve
Ignition	Piezo	Piezo	Piezo
Power Required	None	None	None
Hose/Regulator	20' with Regulator	20' with Regulator	Regulator Only
P.O.L./Excess Flow Check Valve	Yes	Yes	NA
Shipping Size (L x W x H)	12.4" x 10.24" x 34.25"	16.14" x 16.14" x 35.04"	16.14" x 16.14" x 35.04"
Shipping Weight (LBS)	25	42	42
Shipping Cube	1.85	4.24	4.24